

HSS spiraalboren DIN 1869 Type 125-1

2019



Toepassing: Voor het boren van de meest voorkomende materialen.

Boorpunt	Materiaal	Uitvoering	Tophoek	Spiraalvorm
> Ø 3,00mm kruisaanslijping	HSS	Blank	118°	type TS

Verpakking: per stuk.

Artikel nummer	Diameter mm	Totale lengte	Snij lengte	Bruto Prijs	v *
0212510100	1,00	100	60	11,95	v
0212510150	1,50	100	60	13,57	v
0212510200	2,00	125	85	14,18	v
0212510250	2,50	140	95	15,24	x
0212510300	3,00	150	100	16,02	v
0212510310	3,10	155	105	16,02	x
0212510320	3,20	155	105	16,02	v
0212510330	3,30	155	105	16,02	v
0212510350	3,50	165	115	17,58	v
0212510400	4,00	175	120	17,69	v
0212510420	4,20	175	120	17,69	v
0212510450	4,50	185	125	19,87	v
0212510500	5,00	195	135	20,59	v
0212510550	5,50	205	140	27,73	v
0212510600	6,00	205	140	29,41	v
0212510650	6,50	215	150	37,06	v
0212510680	6,80	225	155	40,91	v
0212510700	7,00	225	155	40,91	v
0212510750	7,50	225	155	49,84	v
0212510800	8,00	240	165	52,97	v
0212510850	8,50	240	165	54,64	v
0212510900	9,00	250	175	54,86	v
0212510950	9,50	250	175	56,93	v
0212511000	10,00	265	185	58,10	v
0212511020	10,20	265	185	83,21	x
0212511050	10,50	265	185	83,21	v
0212511100	11,00	280	195	104,37	x
0212511150	11,50	280	195	111,29	x
0212511200	12,00	295	205	137,69	x
0212511250	12,50	295	205	158,73	x
0212511300	13,00	295	205	164,82	x