

## HSS spiraalboren DIN 1869 Type 125-2



02/2025

**Toepassing:** Voor het boren van de meest voorkomende materialen.

Boorpunt	Materiaal	Uitvoering	Tophoek	Spiraalvorm
> Ø 2,00mm kruisaanslijping	HSS	Blank	130°	type TS

**Verpakking:** per stuk.

Artikel nummer	Diameter mm	Totale lengte	Snij lengte	*
0212520150	1,50	150	100	x
0212520200	2,00	160	110	v
0212520300	3,00	190	130	x
0212520350	3,50	210	145	v
0212520400	4,00	220	150	v
0212520450	4,50	235	160	v
0212520500	5,00	245	170	v
0212520550	5,50	260	180	v
0212520600	6,00	260	180	v
0212520650	6,50	275	190	v
0212520680	6,80	290	200	x
0212520700	7,00	290	200	x
0212520750	7,50	290	200	v
0212520800	8,00	305	210	v
0212520850	8,50	305	210	x
0212520900	9,00	320	220	v
0212520950	9,50	320	220	v
0212521000	10,00	340	235	v
0212521050	10,50	340	235	x
0212521100	11,00	365	250	v
0212521150	11,50	365	250	x
0212521200	12,00	375	260	x
0212521250	12,50	375	260	x
0212521300	13,00	375	260	x